



POWERFUL SOLUTIONS IN BATTERY CHARGING

Syracirkulation

Charger: MTM, MTM-HF			Charging algorithm: 10-7 Charging algorithm: 10-8				Charging Factor: 1.05			
Time	5,6	6	7	8	9	10	11	12	13	14
A	hours	hours	hours	hours	hours	hours	hours	hours	hours	hours
20	100	114	140	166	194	224	253	278	304	328
25	125	143	175	208	243	280	316	348	380	410
30	150	171	210	249	291	336	380	417	456	492
40	200	228	280	332	388	448	506	556	608	656
50	250	286	350	416	486	560	632	696	760	820
60	300	342	420	498	582	672	760	834	912	984
80	400	456	560	664	776	896	1012	1112	1216	1312
100	500	570	700	830	970	1120	1265	1390	1520	1640
120	600	684	840	996	1164	1344	1518	1668	1824	1968
125	625	713	875	1038	1213	1400	1581	1738	1900	2050
130	650	741	910	1079	1261	1456	1644	1807	1976	2132
150	750	855	1050	1245	1455	1680	1898	2085	2280	2460
160	800	912	1120	1328	1552	1792	2024	2224	2432	2624
175	875	998	1225	1453	1698	1960	2214	2433	2660	2870
200	1000	1140	1400	1660	1940	2240	2530	2780	3040	3280
225	1125	1283	1575	1868	2183	2520	2846	3128	3420	3690
250	1250	1425	1750	2075	2425	2800	3163	3475	3800	4100
300	1500	1710	2100	2490	2910	3360	3795	4170	4560	4920
Maximal batteristorlek (Kapacitet Ah/5h i tabell ovan) som urladdat med 80% laddas upp på ovanstående tider med de laddare vars märkström visas i vänstra kolumnen.										

2012-08-22/KL

D-3838
Utgåva 2